









# Production S3000

## Type 1 - Windows



mit Pfosten

# CE

ARUTECH PARIMAD AKNAD OÜ  
Peterburi tee 47B,  
11415, Tallinn

11

**EN 14351-1: 2006+A1:2010**

Window and door system  
System GEALAN S 3000 ,  
for residential and non-residential construction







***A profile / B profile***

<b>Air permeability:</b>	4/4
<b>Water tightness:</b>	E 750 / 8A
<b>Resistance to wind load:</b>	C3/B4 // C3/B4
<b>Thermal conductivity <math>U_w</math> *</b>	1,5 W/m <sup>2</sup> K / 1,5 W/m <sup>2</sup> K
<b>Protection against noise:</b>	≤38 dB / ≤38 dB
<b>Hazardous substances:</b>	pole / pole

\* 2k4-16-4sel+arg(24mm)

# Production S3000

## Type 2 - Doors



mit Pfosten

# CE

ARUTECH PARIMAD AKNAD OÜ  
Peterburi tee 47B,  
11415, Tallinn

11

**EN 14351-1: 2006+A1:2010**

Window and door system  
System GEALAN S 3000 ,  
for residential and non-residential construction




***A profile / B profile***

<b>Air permeability:</b>	4
<b>Water tightness:</b>	9A
<b>Resistance to wind load:</b>	C4/B4
<b>Thermal conductivity <math>U_w</math>*</b>	1,6 W/m <sup>2</sup> K
<b>Protection against noise:</b>	≤38 dB
<b>Hazardous substances:</b>	pole

\* 2k4-16-4sel+arg(24mm)

# Production S3000

## Type 3 - Stulp-windows



CE

ARUTECH PARIMAD AKNAD OÜ  
Peterburi tee 47B,  
11415, Tallinn

11

**EN 14351-1: 2006+A1:2010**

Window and door system  
System GEALAN S 3000 ,  
for residential and non-residential construction




***A profile***

<b>Air permeability:</b>	4
<b>Water tightness:</b>	9A
<b>Resistance to wind load:</b>	C4/B4
<b>Thermal conductivity <math>U_w</math> *</b>	1,5 W/m <sup>2</sup> K
<b>Protection against noise:</b>	≤38 dB
<b>Hazardous substances:</b>	pole

\* 2k4-16-4sel+arg(24mm)

# Poduction S3000

## Type 4 - Stulp-doors



CE

ARUTECH PARIMAD AKNAD OÜ  
Peterburi tee 47B,  
11415, Tallinn

11

**EN 14351-1: 2006+A1:2010**

Window and door system  
System GEALAN S 3000 ,  
for residential and non-residential construction


***A profile / B profile***

<b>Air permeability:</b>	4/4
<b>Water tightness:</b>	9A / 9A
<b>Resistance to wind load:</b>	C2/B2 // C1/B2
<b>Thermal conductivity <math>U_w</math> *</b>	1,5 W/m <sup>2</sup> K / 1,5 W/m <sup>2</sup> K
<b>Protection against noise:</b>	≤38 Db / ≤38 Db
<b>Hazardous substances:</b>	pole / pole

\* 2k4-16-4sel+arg(24mm)

# roduction S3000

ype 5 - parallel sliding sloping windows and doors



CE

ARUTECH PARIMAD AKNAD OÜ  
Peterburi tee 47B,  
11415, Tallinn

11

**EN 14351-1: 2006+A1:2010**

Window and door system  
System GEALAN S 3000 ,  
for residential and non-residential construction


***A profile***

<b>Air permeability:</b>	4
<b>Water tightness:</b>	E750
<b>Resistance to wind load:</b>	C2/B3
<b>Thermal conductivity <math>U_w</math> *</b>	1,5 W/m <sup>2</sup> K / 1,5 W/m <sup>2</sup> K
<b>Protection against noise:</b>	≤38 Db
<b>Hazardous substances:</b>	pole

\* 2k4-16-4sel+arg(24mm)

# Production S3000

Type 6 - External doors and terrace doors



CE

ARUTECH PARIMAD AKNAD OÜ  
Peterburi tee 47B,  
11415, Tallinn

11

**EN 14351-1: 2006+A1:2010**

Window and door system  
System GEALAN S 3000 ,  
for residential and non-residential construction

***A profile***

<b>Air permeability:</b>	3
<b>Water tightness:</b>	7A
<b>Resistance to wind load:</b>	C5
<b>Thermal conductivity <math>U_w</math> *</b>	1,6 W/m <sup>2</sup> K / 1,6 W/m <sup>2</sup> K
<b>Hazardous substances:</b>	pole

\* 2k4-16-4sel+arg(24mm)