








# Production S8000IQ Plus IKD SKD

## Type 1 - Windows



mit Pfosten



ARUTECH PARIMAD AKNAD OÜ  
Peterburi tee 47B,  
11415, Tallinn

11

**EN 14351-1: 2006+A1:2010**







Window and door system  
System GEALAN S 8000IQ Plus IKD SKD,  
for residential and non-residential construction

Air permeability:	4
Water tightness:	E750
Resistance to wind load:	C3/B3
Thermal conductivity $U_w^*$	0,77 W/m <sup>2</sup> K
Protection against noise:	pole
Hazardous substances:	pole

\* 3k4-16TGI-4sel-16TGI-4sel (44mm)

# Production S8000IQ Plus IKD SKD

## Type 2 - Stulp-windows and Stulp-doors



ARUTECH PARIMAD AKNAD OÜ  
Peterburi tee 47B,  
11415, Tallinn

11

**EN 14351-1: 2006+A1:2010**

Window and door system  
System GEALAN S 8000IQ Plus IKD SKD ,  
for residential and non-residential construction

<b>Air permeability:</b>	4
<b>Water tightness:</b>	8A
<b>Resistance to wind load:</b>	C1/B2
<b>Thermal conductivity <math>U_w^*</math></b>	0,77 W/m <sup>2</sup> K
<b>Protection against noise:</b>	pole
<b>Hazardous substances:</b>	pole

\* 3k4-16TGI-4sel-16TGI-4sel (44mm)